

■ ■ **MasterDrive OX Series**

SATA Solid State Drive

SATA-II speeds with MLC Flash



Super Talent's MasterDrive OX series SSD brings the solid state drive to a whole new audience. No longer just for the military, enterprise and elite users, the MasterDrive OX SSD is truly affordable. And Super Talent doesn't strip out features to bring down the price. With no-compromise features like SATA-II technology for exceptionally fast read speeds of 150MB/sec, and the same resistance to shock and vibration as all Super Talent's SSDs, the MasterDrive OX SSD delivers the performance and reliability today's mobile enthusiasts demand.

Super Talent's Flash management techniques increase reliability and endurance, and continue to provide unprecedented vibration and shock tolerance. Our software and hardware testing ensures utmost quality of each MasterDrive OX SSD. Super Talent offers a 2 year warranty for the MasterDrive OX SSD.

Physical Specifications

Form Factor	2.5"
*Capacity	16GB - 256GB
Dimension	69.85mm x 100.20mm x 9.50mm
SATA Interface	Serial ATA-II
NAND Flash	MLC
Power Supply	5.0V _{cc} ± 5%
Package	Complete metal housing

Endurance Specifications

Read	Unlimited	
Write	16GB	8.8 yrs @ 50GB write-erase/day
	32GB	17.5 yrs @ 50GB write-erase/day
	64GB	35.1 yrs @ 50GB write-erase/day
	128GB	70.1 yrs @ 50GB write-erase/day
	256GB	140.2 yrs @ 50GB write-erase/day

Reliability Specifications

MTBF	+1,000,000 hours
Data Reliability	Built-in EDC/ECC function
Data Integrity	5 years
Wear Leveling Algor.	Patent Pending

Performance Specifications

Seq. Read	150 MB/sec (max)
Seq. Write	100 MB/sec (max)
Access Time	0.1 ms

Environmental Specifications

Operating Shock	1500G
Operating Vibration	16G
Operating Temp.	0°C to +70°C

Ordering Information

16GB	FTM16GL25H
32GB	FTM32GL25H
64GB	FTM64GL25H
128GB	FTM28GL25H
256GB	FTM56GL25H

■ MasterDrive OX Series

SATA Solid State Drive

SATA Flash Drive Pin Assignment

Power Segment

PIN	Signal Name	Description
P1	Not Used (3.3V)	N/A
P2	Not Used (3.3V)	N/A
P3	Not Used (3.3V Precharge)	
P4	GND	1 st mate
P5	GND	2 nd mate
P6	GND	
P7	5V Precharge	5V Power
P8	5V Precharge	5V Power
P9	5V Precharge	
P10	GND	
P11	Reserved	
P12	GND	1 st mate
P13	Not Used (12V Precharge)	N/A
P14	Not Used (12V)	
P15	Not Used (12V)	

Signal Segment

PIN	Signal Name	Description
S1	GND	
S2	RxP	Differential Signal pair for Receive
S3	RxN	
S4	GND	
S5	TxN	Differential Signal pair for Transmit
S6	TxP	
S7	GND	

Revision History

August 11, 2008 Rev-A Preliminary Product Specification Released
December 8, 2008 Rev-B Added 256GB

■ MasterDrive OX Series

SATA Solid State Drive

Mechanical Descriptions

