

550W / 650W / 750W



#### Introduction

LLC topology and all Japanese e-capacitors make Hydro GSM PRO series a perfect solution for your power-hungry components, which realize ultra-high efficiency as well as extraordinary performance. The intelligent 120mm thermal control fan allows optimal cooling air to be drawn in to the PCB board, making it almost impossible to heat. In terms of the product look, Hydro GSM PRO is coated with matte black finish and mounted with octagonal stainless fan grill that enables excellent airflow while remaining stylish for PC gamers.

#### **Features**



#### **LLC Topology**

To optimize your power conversion efficiency



#### +12V Single Rail Design

Designed for power- intensive VGA cards Provides strong power to any overloading condition



#### Thermal Control Fan

An advanced thermal control fan makes optimal · Intel Latest CPU ready cooling and reduces noise.

- Compliance with the newest ATX 12V V2.52
- · Efficiency ≥ 90% at typical load
- · Intelligent fan speed control
- · Quiet and long-lasting 120mm silent fan
- · Ribbon cables for all enthusiasts
- · Powerful single +12V rail design
- · All Japanese electrolytic capacitors
- · Full protections OCP, OVP, SCP, OPP, OTP



#### DC to DC Module Design

Providing high efficient, stable power.



550W / 650W / 750W





550W / 650W / 750W


#### **Product Overview**





Japanese e-capacitors have better quality, protecting your equipment from the infamous capacitor leakage problem and also increasing the life-span of your equipment

Single +12V rail



Multi.+12V rail



#### **Custom DC-DC Module**


DC to DC modules to improve the reliability, and enable greater compatibility with low ripple noise to effectively reduce interference of system components, prolonging system lifetime.


#### **Unleash +12V Power Output**


VGA card is a power-hungry component that needs most power. A single +12V rail design can deliver stable power and avoid any overloading conditions.


550W / 650W / 750W


#### **Performance**
















550W / 650W / 750W

#### **Rating**

550W

| AC Input           | 100-240V~, 8-4A ,50-60Hz |     |        |      |       |
|--------------------|--------------------------|-----|--------|------|-------|
| DC Output          | +3.3V                    | +5V | +12V   | -12V | +5Vsb |
| Max Output Current | 20A                      | 20A | 45.83A | 0.3A | 3.0A  |
| Max Combined Power | 100W                     |     | 550W   | 3.6W | 15W   |
| Total Power        | 550W                     |     |        |      |       |

650W

| AC Input           | 100-240V~, 8-4A ,50-60Hz |     |          |      |       |
|--------------------|--------------------------|-----|----------|------|-------|
| DC Output          | +3.3V                    | +5V | +12V     | -12V | +5Vsb |
| Max Output Current | 20A                      | 20A | 54.17A   | 0.3A | 3.0A  |
| Max Combined Power | 100W                     |     | 650W     | 3.6W | 15W   |
| Total Power        | 650W                     |     |          |      |       |
|                    |                          |     | <u> </u> |      |       |

750W

| AC Input           | 100-240V~, 10-5A ,50-60Hz |     |       |      |       |
|--------------------|---------------------------|-----|-------|------|-------|
| DC Output          | +3.3V                     | +5V | +12V  | -12V | +5Vsb |
| Max Output Current | 20A                       | 20A | 62.5A | 0.3A | 3.0A  |
| Max Combined Power | 100W                      |     | 750W  | 3.6W | 15W   |
| Total Power        | 750W                      |     |       |      |       |

550W / 650W / 750W

#### **Connectors**


|         | 550W | 650W | 750W |
|---------|------|------|------|
|         | 1    | 1    | 1    |
| 24 PIN  |      |      |      |
|         | 2    | 2    | 2    |
| 4+4 PIN |      |      |      |
|         | 4    | 4    | 4    |
| 6+2 PIN |      |      |      |
|         | 8    | 8    | 8    |
| SATA    |      |      |      |
|         | 3    | 3    | 3    |
| MOLEX   |      |      |      |
|         | 1    | 1    | 1    |
| FLOPPY  |      |      |      |



550W / 650W / 750W

#### **Cable Length**

#### 550W / 650W / 750W





550W / 650W / 750W

#### **Specifications**



|                   | 550W                                | 650W  | 750W              |  |  |
|-------------------|-------------------------------------|-------|-------------------|--|--|
| Model             | HGS-550M HGS-650M                   |       | HGS-750M          |  |  |
| Туре              | ATX                                 |       |                   |  |  |
| PFC               | Active PFC                          |       |                   |  |  |
| Input Voltage     | 100V~240V                           |       |                   |  |  |
| Input Current     | 8-4A                                | 10-5A |                   |  |  |
| Input Frequency   | 50~60Hz                             |       |                   |  |  |
| Output Capacity   | 550W 650W                           |       | 750W              |  |  |
| Max. Output Power | 550W 650W                           |       | 750W              |  |  |
| Fan Type          | Silent Fan, 120mm Silent Fan, 120mm |       | Silent Fan, 120mm |  |  |
| Efficiency        | 90%                                 |       |                   |  |  |
| MTBF              | 100,000 Hrs                         |       |                   |  |  |
| Protection        | OCP,OVP, SCP,OPP,OTP                |       |                   |  |  |
| Weight            | kgs kgs kgs                         |       | kgs               |  |  |
| Dimension(L×W×H)  | 150 x 140 x 86mm                    |       | 150 x 140 x 86mm  |  |  |



#### **Package Information**

| Model                         | HGS-550M                                | HGS-650M       | HGS-750M       |  |  |
|-------------------------------|---|----------------|----------------|--|--|
| EAN Code                      | 471322452381 6                          | 471322452380 9 | 471322452379 3 |  |  |
| UPC Code                      | 84568501103 9 84568501102 2 84568501101 |                |                |  |  |
| Shipping Dimensions (L×W×H)   | mm                                      |                |                |  |  |
| Shipping Weights              | kg kg kg                                |                |                |  |  |
| Master Pack Dimension (L×W×H) | mm                                      |                |                |  |  |
| Master Pack Quantity          | 10 retail boxes per master package      |                |                |  |  |
| Master Pack Weight            | kg kg kg                                |                |                |  |  |
| Pallet Quantity               | pcs                                     |                |                |  |  |
| Country of Origin             | China                                   |                |                |  |  |
| Warranty                      | 7 Years                                 |                |                |  |  |
| Additional Information        |   |                |                |  |  |