



AT-ARW256E Wireless ADSL Router

AT-ARW256E

IEEE 802.11g wireless ADSL bridge/router with 4 Ethernet ports and 1 USB port

High Bandwidth Access to the Internet and Corporate LAN

The AT-ARW256E is the perfect solution for the small office or branch office that wants to use high-speed, 'always on' ADSL services to access the Internet or other corporate locations. Combining a wireless access point, ADSL modem, IP router, 4 port 10/100TX switch and Stateful Inspection Firewall into one affordable unit, the AT-ARW256E provides the ideal solution for bandwidth-hungry end-users and ADSL service providers who need security. The AT-ARW256E is easily installed over an existing analog line, supporting standard POTS operation together with state-of-the-art ADSL services. Applications include data intensive office use, fast web download, Video-on-Demand, video streaming and telecommuting via Virtual Private Network (VPN). VPN operation is supported using IPSec, PPTP and L2TP pass-through.

Business-class Stateful Inspection Firewall

Because ADSL offers an 'always on' connection, users are actually more at risk using this service than with conventional modem dial-up. To counter this threat, the AT-ARW256E is equipped with a powerful Stateful Inspection Firewall that protects against malicious attacks from the Internet – giving peace of mind security for the home and office LAN. Network Address Translation (NAT) also 'hides' all LAN users behind one public IP address, protecting the LAN from external hackers. Single PPTP or multiple IPSec and L2TP sessions are supported using the AT-ARW256E's sophisticated pass-through capability; standard NAT limitations are no longer a barrier for the power user.

The Service Provider's Choice

The AT-ARW256E is ADSL2 and ADSL2+ compliant, supporting up to 12Mbps and 24Mbps downstream data rates respectively. Using industry-standard Discrete Multi-Tone (DMT) technology, the AT-ARW256E supports network speeds up to 8Mbps downstream and up to 1Mbps upstream. Alternatively, G.lite is supported for applications where minimum cost and tool-free installation is required. Close partnering with Digital Subscriber Line Access Multiplexer (DSLAM) vendors ensures the highest levels of interoperability for service providers, with extensive ADSL testing being carried out. Built-in support for PPP over Ethernet (PPPoE) and PPP over ATM (PPPoA) provides full compatibility with existing ISP dial-up systems. Bridged Ethernet and IP over ATM complete the range of flexible and robust network connectivity options. Superior rate/reach performance ensures that service providers and users alike enjoy maximum data throughput at maximum line-lengths from the exchange.

Easy to Set Up

Installation takes a matter of minutes using the simple, browser-based configuration interface. Standard cabling is used to connect to the Ethernet LAN and ADSL. All cables, including USB, are supplied with the product. All TCP/IP operating systems are supported, including Windows, Linux and Mac. An integral DHCP server provides automatic IP address assignment to all PCs on the LAN to minimize network administration. Both static and dynamic IP address assignment are supported on the ADSL interface, so that all connection modes are supported.

Up to 253 LAN Users Can Share One Line and One IP Address

The AT-ARW256E supports up to 253 LAN-attached users – easily enough for a small office, while high-speed ADSL services mean that they can all share a single line and still have plenty of performance. NAT allows 253 users to share one public IP address for low-cost Internet access.

Key Features

- IEEE 802.11, 802.11b and 802.11g compliant
- Conforms to Wireless Ethernet Compatibility Alliance (WECA) and Wireless Fidelity (Wi-Fi) standards
- Supports IEEE 802.11b and 802.11g simultaneously
- Supports seamless WLAN roaming
- Supports Direct Sequence Spread Spectrum (DSSS) technology
- High-speed ADSL connectivity with integral 4 port switch
- Supports RE-ADSL2/2+, ADSL2/2+, G.dmt.bis, G.lite.bis, G.dmt and G.lite ADSL standards, Annex A
- Supports ADSL standards Annex L and Annex M
- Up to 24Mbps downstream, and up to 3.5Mbps upstream data rate
- 1 x ADSL2/2+ port
- 1 x USB port
- 4 x 10/100 Ethernet ports
- Network Address Translation (NAT)
- Integral Stateful Inspection Firewall
- IPSec, PPTP and L2TP VPN pass-through
- Dynamic port opening for gaming applications
- Browser-based GUI
- PAP/CHAP/MS-CHAP authentication
- Dynamic IP address assignment
- Static IP address assignment
- Dynamic Host Configuration Protocol (DHCP) server/relay/client
- SNMP v1 and v2c
- Compact form factor
- Flash upgradable

AT-ARW256E | Wireless ADSL Router

Intelligent ADSL Rate Adaptation

The upstream and downstream data rates are dynamically allocated by the AT-ARW256E to minimize noise and maximize service reliability. For each session, the ADSL connection speed is automatically reconfigured to achieve maximum data throughput (within the limits imposed by the service provider).

Flash Software Update

The AT-ARW256E can be upgraded simply and quickly by loading new firmware into flash memory using the simple, browser-based application. New enhancements can be loaded into the unit in a matter of minutes.

Main Features

ADSL/ATM Support

ANSI T1.413-1998 Issue 2, ITU-T G.992.1 (G.dmt), G.992.2 (G.lite), G.992.3 (G.dmt.bis), G.992.4 (G.lite.bis), G.992.5 (ADSL2+), G.992.3/4 Annex L (RE-ADSL2), G.992.5 Annex L (RE-ADSL2+) and G.992.5 Annex M compliant

Rate adaptive modem at 32kbps steps

Dynamic adaptive equalization to improve carrier's service area

Bridge Tap Mitigation

ATM layer with traffic shaping QoS (UBR, CBR, VBR-rt, VBR-nrt)

AAL ATM attributes — AAL5

Multiple PVC up to 8 (bridged)

Spectral compatibility with POTS

F5 OAM loopback/send and receive

Encapsulation Support

RFC 2684 bridge and routed LLC and VC Mux

RFC 2364 PPPoA client

RFC 2516 PPPoE client

RFC 2225/1577 classical IP

Transparent bridge

PAP/CHAP/MS-CHAP for password authentication

Network Support

Static IP, Dynamic RIP routing

IP/TCP/UDP/ICMP/ARP/RARP application

Network Address Translation (NAT)

Port mapping/forwarding

Easy setup of port forwarding rules for popular games/applications

NAT application level gateway for popular applications

DHCP server/relay/client

DNS relay agent

Dynamic DNS (DDNS)

DMZ

IPSec and PPTP/L2TP VPN pass-through

PPP always-on with configurable timeout

PPP Dial-on-Demand

Universal Plug and Play (UPnP)

TR-069

WLAN Support

IEEE 802.11, 802.11b and 802.11g compliant

Conforms to Wireless Ethernet Compatibility Alliance

(WECA) and Wireless Fidelity (Wi-Fi) standards

Supports IEEE 802.11b and 802.11g simultaneously

Supports seamless WLAN roaming

Frequency band:

- 2412MHz — 2462MHz (North America/FCC)

- 2412MHz — 2472MHz (ETSI/Europe)

- 2412MHz — 2484MHz (Japan)

- 2457MHz — 2472MHz (France)

- 2457MHz — 2462MHz (Spain)

Supports Direct Sequence Spread Spectrum (DSSS) technology

Modulation: OFDM with BPSK, QPSK, 16QAM, 64QAM,

DBPSK, DQPSK, CCK

Wireless media access protocol: CSMA/CA with ACK

Dynamic rate scaling: 54, 48, 36, 24, 12, 11, 9, 6, 5.5, 2 and 1Mbps

Operating range: >300m (Open Air)

Management Support

Web-based HTTP management GUI

Web-based firmware upgrade (local)

Soft factory reset button via web GUI

Diagnostic test (DSL, OAM, Network, Ping)

Telnet/CLI

Syslog

Firmware upgradable for future feature enhancement

Security Support

NAT for basic firewall

Packet filtering firewall

Stateful Packet Inspection

Protection against Denial of Service attacks

Password authentication to modem

Hardware

Texas Instrument TNETD7300 single chip network

Processor/AFE/line driver chipset

Marvell 88E6060-RJ 5+1 Port 10/100 MAC/PHY switch

(Auto MDI/MDI-X)

Texas Instrument TNETW1130 based IEEE 802.11b/g

MiniPCI Daughterboard

USB 1.1 compliant

4MB Flash ROM

16MB SDRAM

Dying Gasp

ITU K.21

GDT

Platform Support

OS independent for Ethernet and WLAN

Windows 98SE/2000/Me/XP/2003 for USB

Power Requirements

Input voltage: 9vDC +/- 10%

Input current: 1.0A

Physical Specifications

LED Indicators

1 x Power

4 x Ethernet

1 x Wireless

1 x USB

1 x DSL

1 x Internet

External Connectors

1 x ADSL/2/2+ port (RJ-11)

1 x USB 1.1 port (Type B)

1 x Reset button (restore to factory defaults)

4 x Ethernet 10/100 port (RJ-45; Auto MDI/MDI-X)

1 x DC power jack (9V)

1 x Power on/off switch

1 x Coaxial connector for detachable, 180° rotatable,

2.4GHz, 3dBi antenna

Measurements

Dimensions: 17.65(L) x 11.89(W) x 3.79(H) cm

Weight: Approx. 350g

Environmental Characteristics

Operating temperature: 0°C to 40°C

Non-operating temperature: -25°C to 70°C

Operating humidity: 30% to 80% relative humidity (non-condensing)

Non-operating humidity: 30% to 95% relative humidity (non-condensing)

Ordering Information

AT-ARW256E-xx

Wireless ADSL bridge/router, Annex A

(4 Ethernet 10/100 ports, 1 USB port)

Where xx = 10 for US power adapter
30 for UK power adapter
40 for Australian power adapter
50 for European power adapter

USA Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2008 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000033 Rev.1